

PRODUCT DESCRIPTION

Kamaz Lubricants HD 40 is a high-quality mono-grade engine oil. HD 40 formulated using highly refined mineral base stocks and carefully selected additives package.

FEATURES AND BENEFITS

- Provide significantly improved protection against varnish
- Protection of engine against high and low temperature deposits
- Oxidation protection.

APPLICATION

Kamaz Lubricants HD 40 is designed to be used commercial vehicles with diesel supercharged engines under severe conditions. These oils are also recommended for diesel engines of commercial vehicles and passenger cars, naturally aspirated petrol engines in accordance with OEM recommendation.

MEETS REQUIREMENTS

API SF

TYPICAL TEST DATA

PROPERTY	TEST METHOD	POWERX HD 40
Density at 20 °C, kg/m ³	GOST 3900 / ASTM D4052	890
Kinematic viscosity at 100 °C, mm ² /s	GOST 33 / ASTM D445 / GOST R 53708	12.5-16.3
Viscosity index	GOST 25371 / ASTM D2270	95
Total base number, mg KOH/1 g oil	GOST 30050 / ASTM D2896	7.0-10.0
Pour Point, °C	GOST 20287 B	-18
Flash Point, °C	GOST 4333 / ASTM D92	240
Sulphated ash, %	GOST 12417 / ASTM D874	1.2
Noack evaporation loss, %	ASTM D5800	6.4

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances.