

PRODUCT DESCRIPTION

Kamaz Lubricants HD 60 is a high-quality mono-grade engine oil. HD 60 formulated using highly refined mineral base stocks and carefully selected additives package.

FEATURES AND BENEFITS

- Provide significantly improved protection against varnish
- Protection of engine against high and low temperature deposits
- Oxidation protection.

APPLICATION

Kamaz Lubricants HD 60 is designed to be used commercial vehicles with diesel supercharged engines under severe conditions. These oils are also recommended for diesel engines of commercial vehicles and passenger cars, naturally aspirated petrol engines in accordance with OEM recommendation.

MEETS REQUIREMENTS

API SF

TYPICAL TEST DATA

PROPERTY	TEST METHOD	POWERX HD 60
Density at 15 °C, kg/m ³	ASTM D1298 / ASTM D4052	903
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	22.0-25.0
Viscosity index	ASTM D2270	94
Total base number, mg KOH/1 g oil	ASTM D2896	7.0-10.0
Pour Point, °C	GOST 20287 B	-18
Flash Point, °C	ASTM D92	255
Sulphated ash, %	ASTM D874	1.2
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	3.0

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances.