

PRODUCT DESCRIPTION

Kamaz Lubricants 0W20 is a fully synthetic multigrade engine oil with excellent fuel economy performance. This oil is formulated to be used in modern high performance engines of passenger cars and light commercial vehicles.

FEATURES AND BENEFITS

- Excellent fuel economy performance
- Excellent low temperature pumpability and engine cold start
- Highest engine wear protection at severe operating conditions of the city cycle
- Excellent detergent-dispersant properties
- Compatible with modern exhaust after treatment systems
- Using the best performance additives technology

APPLICATION

Recommended for all-season operation in gasoline engines of the modern Japanese, American and Korean vehicles where usage of API SN/CF and/or ACEA A1/B1 performance oils is required.

MEETS REQUIREMENTS

ACEA C3
 ILSAC GF-5
 GM dexos2
 Chrysler MS-6395
 GM 6094M
 API SN/CF

TYPICAL TEST DATA

PROPERTY	TEST METHOD	PRESTOX 0W20
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	5,6-9,3
Viscosity index	ASTM D2270	156
Cold Cranking Viscosity (CCS) at -30 °C, mPa·s	ASTM D5293	4,038
Borderline Pumping Viscosity (MRV) at -35 °C, mPa·s	ASTM D4684	18,600
Total base number, mg KOH/1 g oil	ASTM D2896	8.0-11.0
Sulphated ash, %	ASTM D874	0.7
Noack evaporation loss, %	ASTM D5800	11.3
Flash Point, COC, °C	ASTM D92	228
Pour Point, °C	ASTM D97	-45

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances.