

PRODUCT DESCRIPTION

Kamaz Lubricants 5W40 is a fully synthetic engine oil for modern gasoline and diesel engines of passenger cars. Formulated with high-quality synthetic base oils in combination with advanced additives technology.

FEATURES AND BENEFITS

- Promotes reliable engine protection
- Helps to reduce the formation of deposits and keeps the engine clean
- Excellent resistance to oxidation and corrosion.

APPLICATION

Recommended for all-season use in gasoline and diesel engines (without Diesel Particulate Filters) required engine oil with API SN and/or ACEA C3 performance level and SAE 5W-40 viscosity.

MEETS REQUIREMENTS

MB-Approval 226.5/229.5
 ACEA C3, GM dexos2
 VW 505 00/50501, Ford WSS-M2C917-A
 Renault RN 0700/0710
 PJSC «AVTOVAZ»
 API SN

TYPICAL TEST DATA

PROPERTY	TEST METHOD	PRESTOX 5W40
Density at 15 °C, kg/m ³	ASTM D1298 / ASTM D4052	848.1
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	12.5-16.3
Viscosity index	ASTM D2270	176
Dynamic viscosity (CCS) at -30°C, mPa·s	ASTM D5293 / GOST R 52559	5800
Dynamic viscosity (MRV) at -35°C, mPa·s	ASTM D4684 / GOST R 52257	29.300
Total base number, mg KOH/1 g oil	ASTM D2896	8-11
Sulphated ash, %	ASTM D874	0.9
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	10
Flash Point, COC, °C	ASTM D92	235
Pour Point, °C	GOST 20287 B	-40

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances.