

## High Performance Fluid For Passenger Car And Commercial Vehicles Automatic Transmissions

### PRODUCT DESCRIPTION

Vertex ATF DX VI is a high quality universal automatic transmission fluid. This fluid was designed in respect of tough demands of leading world original equipment manufacturers and suitable for use in both of conventional and modern types of automatic transmission.

### APPLICATION

Vertex ATF DX VI is recommended for step-type passenger car and commercial vehicles automatic transmissions where Dexron® IIIH or previous performance levels are required. It also can be used as power steering fluid.

### MEETS REQUIREMENTS

MB-Approval 236.12/236.14/236.15/236.41  
ZF TE-ML 04D, 14B, 16L, 20B (ZF001944)  
Volvo 97341  
MAN 339 Types L1, V2, Z2, Z11  
Voith H55.6336.xx

GM Dexron IIIH, IIIG, IID  
Ford Mercon V  
Ford Mercon  
Allison C-4, TES-295, TES-389  
JASO 1-A  
Volvo 97340

### TYPICAL TEST DATA

PROPERTY	TEST METHOD	VERTOX ATF DX VI
Kinematic Viscosity at 100 °C, mm <sup>2</sup> /s	ASTM D 445	5.9
Viscosity Index	ASTM D 2270	148
Brookfield Viscosity at -40 °C, mPa·s	ASTM D 2893	12300
Brookfield Viscosity at -20 °C, mPa·s	ASTM D 2893	1080
Pour Point, °C	ASTM D 97	216
Density at 15 °C, kg/m <sup>3</sup>	ASTM D 1298	849

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances.