

GEARE X SAE 90

High Quality Gear Oil

PRODUCT DESCRIPTION

Kamaz Gearex SAE 90 oil is oxidation inhibited gear oils that are recommended for many automotive and industrial equipment. Using highly refined base stocks combined with oxidation inhibitor additives, Kamaz Gearex GL-1 gear oils are ideal for use in automotive and industrial gearboxes and manual transmissions where API GL-1 mineral, non-EP gear oils are recommended.

APPLICATION

Intended for use in manual transmissions, axles and final drives requiring API GL-1 level performance, on-highway light and heavy duty trucks, busses and vans, off-highway industries including: construction, mining, quarrying, and agriculture and lightly loaded industrial gears. Not recommended for use in automotive or heavy duty differentials using offset spiral bevel (hypoid) gear sets where API GL-4 or API GL-5 gear oils are specified by the manufacturer.

MEETS REQUIREMENTS

API GL-1

TYPICAL TEST DATA

PROPERTY	TEST METHOD	GEAREX SAE 140
Kinematic Viscosity at 100 °C, mm2/s	GOST 33 / ASTM D445 / GOST R 53708	18
Viscosity Index	GOST 25371 / ASTM D2270	90
Flash Point COC, °C	GOST 4333 / ASTM D92	271
Pour Point, °C	GOST 20287 B/ASTM D97	-16

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances.

Moscow, Russia v.1.4.11.02.2018